

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/090647 A1

(51) International Patent Classification⁷: **C25D 17/22**,
17/24, 19/00

(21) International Application Number:
PCT/IT2004/000145

(22) International Filing Date: 23 March 2004 (23.03.2004)

(25) Filing Language: Italian

(26) Publication Language: English

(71) Applicants (for all designated States except US): **GLO-
MAX S.R.L.** [IT/IT]; Via Del Commercio 46, I-20040 Bel-
lusco (IT). **LM FINISHING SYSTEMS S.R.L.** [IT/IT];
Via Strada del Confine 35/a, I-36056 Belvedere di Tezze
sul Brenta (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SPINA, Umberto**
[IT/IT]; Via Torri Bianche 5, I-20059 Vimercate (IT).
LANDO, Walter [IT/IT]; Via Strada del Confine 35,
I-36056 Belvedere di Tezze sul Brenta (IT).

(74) Agent: **CONCONE, Emanuele**; Società Italiana Brevetti
S.p.A., Via Carducci, 8, I-20123 Milano (IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PROCESS AND APPARATUS FOR THE ELECTROGALVANIC COATING OF METAL ITEMS



(57) Abstract: In a process for the electrogalvanic coating of metal items through a sequence of chemical or electrochemical treat-
ment phases, each of said treatment phases includes the following steps: a) introducing the drum containing the items into a cen-
trifuge; b) delivering a first chemical treatment liquid to the centrifuge; c) carrying out the treatment; d) draining said first chemical
treatment liquid from the centrifuge; e) carrying out a centrifugation of the items to recover said liquid; f) delivering washing water
to the centrifuge; g) carrying out the washing; h) draining the washing water from the centrifuge; i) carrying out a centrifugation of
the items to recover said liquid; j) transferring the drum to another station, or repeating the preceding steps with another chemical
treatment liquid. Carrying out the washing subsequent to a chemical treatment phase in the same station where the treatment has been
carried out allows to significantly reduce the number of stations, moreover the centrifugation subsequent to every treatment or wash-
ing allows to recover the liquids thus reducing the consumption thereof, as well as to prevent the problems of liquid carry-over from
one station to another, which also prevents the environmental pollution. A plant that embodies said process consists of a sequence
of aligned stations (A), with an automatic loading station at the inlet and an automatic unloading station at the outlet, in which the
items to be treated are contained in perforated cylindrical drums (D) open at the top that are automatically moved from one station to
another by means of carriages (C) that run on rails (B) extending above the stations along the whole length of the plant. The use of
open drums (D), instead of the conventional barrels closed by a door, allows to carry out in a completely automatic way the loading
and unloading of the items in the plant end stations with a great saving of labour force as well as with no risks to the health of the
operators.

WO 2005/090647 A1